

300W~305W

Monocrystalline silicon Light weight flexible solar panel



Key Features

Lightweight

Optimized composite materials, 60% lighter at the same power

Flexible

Special manufacturing process and materials provide bending ability

Excellent Appearance and Performance

Esthetics module design, no flare effect, "0" risk of micro crack

Easy transportation and installation

Original design making it far less costly for transportation and installation

Customization

Customization for various senarios, high additional value


Superior Low Irradiance Performance

Excellent low irradiance performance, increase power generation in low-light conditions like mornings, evenings and cloudy days

Quality system: ISO 9001: 2005



Linear Performance Warranty





Leading product and power warranty

12 Materials and workmanship warranty


25 Linear power warranty

The size of module





Characteristic Curves



Electrical Characteristics

| STC | PURES-300W | PURES-305W | |
|---|------------|---------------|--|
| Maximum Power (Pmax) | 300W | 305W | |
| Maximum Power Voltage (Vmp) | 23.2V | 23.3V | |
| Maximum Power Current(Imp) | 12.95A | 13.08A | |
| Open-circuit Voltage (Voc) | 27.6V | 27.6V | |
| Short-circuit Current(Isc) | 13.95A | 14.00A | |
| Module Efficiency(%) | 19.78% | 20.10% | |
| Operating Temperature | -40 °C | -40 ℃ to 85 ℃ | |
| Maximum System Voltage | 100 | 1000VDC | |
| Maximum Series Fuse Rating | 2 | 20 A | |
| Application Cla ss | CI | Class A | |
| Power Tolerance | 0^ | ~+5 W | |
| STC:Irradiance 1000W/m² , module temperature 25℃ ,AM= | 1.5 | | |
| | | | |

Mechanical Characteristics

| Solar Cell | Monocrystalline sillicon cell |
|-------------------|--------------------------------------|
| Cell Size | 182×91mm |
| No. of cells | 80 |
| Module Dimensions | L:1945*W:780*H:3 mm |
| | L:1945*W:780*H:18 mm(J-Box included) |
| Weight | 5.2kg |
| Backsheet | White PV Backsheet |
| J-Box | IP 67 |
| Output cables | 4mm² |
| Cable length | (+)/(-) 300 mm |
| Connector | MC4 compatible |
| | |

Temperature Characteristics

| NOCT(Nominal Operating Cell Temperature) | 41 ± 2℃ |
|--|-----------|
| Temperature Coefficient of Pmax | -0.38%/°C |
| Temperature Coefficient of Voc | -0.28%/°C |
| Temperature Coefficient of Isc | 0.020%/℃ |

Packaging

| Container | 20'GP | 40'HQ | |
|----------------------|-------|-------|--|
| Pieces per pallet | 35 | 35 | |
| Pieces per container | 350 | 770 | |

